

Seeker SE

Leakage Detector

- High Performance, Frequency-Settable Leakage Detector
- Ideal for Drive-Outs, Pinpointing Leak Location, and Troubleshooting
- Large Numerical Measurement Display
- Sensitive, Stable Measurements, Channel Tag Compatible

The Seeker SE™ is a frequency-agile leakage detector specifically designed for efficient distribution leakage management, displaying numerical measurements of leaks on up to ten selectable channels, and emitting a tone proportional to leak strength.

Mobile or Hand-Held

The Seeker SE may be used in its mobile mount (included) for drive-outs, or easily removed from the mount for leakage troubleshooting on foot with a rubber duck antenna (included), or optional dipole antenna.

Stable, repeatable readings, multi-frequency operation, and leakage recording simplify leak location and documentation.

Comprehensive Coverage

Durable, simple to use, and very cost-effective, the Seeker SE is the intermediate solution offered in the line of Trilithic leakage products, which includes the popular Seeker Lite™ installation leakage detector, Seeker™ and the Seeker GPS™.

A workforce that includes any of these leakage measurement instruments ensures leakage-free networks from subscriber to head-end.

Flexibility

With the initial Seeker SE costs being scalable for any number of vehicles, the Seeker Family of leakage detectors offers an unprecedented level of customizable, fleet-based leakage detection options. You can start from manual leakage detection with the Seeker SE alone and later upgrade the Seeker SE to a Seeker GPS for fully automated find and fix leakage management with Leakage Analysis Workshop™ (LAW) software.



Channel Tag Compatible

The Seeker SE includes technology compatible with the Trilithic CT-2™ or CT-3™ channel taggers. The Trilithic CT-2 or CT-3 channel tagger is installed in the head-end and used with Trilithic's leakage receivers to help identify leakage sources in overbuilt areas, to increase detection range, and to increase immunity to interference.

Data Management

The Seeker Setup™ software configures the Seeker SE, enabling operators to assemble files containing channel frequencies, squelch levels, and other settings. With this software, the operator can efficiently download configurations to one or more leakage detectors.

Seeker SE

Leakage Detector

SPECIFICATIONS

Frequency Range	Low band: 109.25 to 110.5 MHz High band: 118.5 to 147.25 MHz Settable using the Seeker Setup software, in 6.25 KHz steps
Frequency Settings	10 user-set operating frequencies, selectable on front panel Selections loaded into detector using Seeker Setup configuration software
Calibrated Level Range	2 to 2000 $\mu\text{V/m}$ Can freeze current numeric reading
Numerical Display	Readout of any detected leakage within sensitivity range
Audible Tone	Tone is present if leakage amplitude exceeds squelch setting Pitch is proportional to strength of leak
Automatic Noise and Overbuild Discrimination	Internal circuitry discriminates between leaks and noise Overbuild discrimination requires the CT-2 or CT-3 channel tagger to be installed in the hub or head-end
Data Connection	Mini-USB connection for setup
Power	Internal battery with eight hours of operation per charge
Options	Semi-rigid protective holster with belt loop
Supporting Software	Seeker Setup software for configuring the Seeker SE for leakage detection

INCLUDES THE FOLLOWING:

Seeker SE leakage detector
P/N 2011073102

Rubber duck antenna

Battery charger

I/O-20 mini-USB charge/data cable

SMB-2 mobile mount

Mobile mount power cable

User's manual and software drivers on CD

UPGRADE:

Field Upgrade to Seeker enabling MCA Communications
P/N 0930114199

OPTIONAL ACCESSORIES:

CC-28 padded holster
P/N 2131249000

CL-9 vehicle power adapter
P/N 0610169007

RELATED ITEMS:

AFS-2 dipole antenna
P/N 2010436000

APM-2 permanent mount, vertical quarter-wave whip antenna (108 to 118 MHz)
P/N 2010649000

APM-3 permanent mount, vertical quarter-wave whip antenna (119 to 160 MHz)
P/N 2010650000

AVM-2 magnetic base, vertical quarter-wave whip antenna (108 to 118 MHz)
P/N 2010380000

AVM-3 magnetic base, vertical quarter-wave whip antenna (119 to 160 MHz)
P/N 2010379000

Seeker pole mounting kit
P/N 2071802000

NFP-1 near field probe
P/N 2010477000

CT-2 channel tagger
P/N 2010670001

CT-3 channel tagger
P/N 2010762000